OMRON

Programmable Slaves CPN2C-S1 OC-DRT

Slaves with the Complex Functionality Needed for Distributed Blocks

Programmable Slaves combine devices, such as sensors and actuators, into one functional unit that is treated as a DeviceNet slave.

Programmable Slaves greatly facilitate device distribution and functional organization. They help standardize programming between units and reduce the amount of programming required at the master.

I/O and operational checks can be performed for each functional unit, rather than waiting for final system assembly, as with conventional distributed I/O systems.

• A Programmable Slave can be programmed from a CX-Programmer up to 3 network levels away. (Includes the DeviceNet network itself. Possible only with CX-Programmer Ver. 2.1 or later and a Programmable Slave Ver. 1.04 or later.)

DeviceNet Slave Functions

Multiword I/O links and explicit messages are used to control slaves from the master. Log data for communications can be sent in one operation whenever necessary using explicit messages.

CompoBus/S Master Functions

Less wiring is required for terminal block expansions, connections to remote devices (such as signal lights or pushbutton switches), and connections to pneumatic valves and other non-OMRON products. Connect using VCTF cable or Special Flat Cable, which allows easy branching.

• RS-232C Communications

Connected to bar code readers, Programmable Terminals, and other devices, the Programmable Slave processes data locally to reduce the load on the master.

• Expansion Units (3 max.)

Just one Unit is required for each distributed block, reducing the number of interfaces for multipoint communications to, in turn, reduce costs.

Ordering Information

Unit type		Input	Output	Clock	Model
10 I/O points 6 inputs; 4 outputs	Connector	6 points: 24 VDC	4 points: transistor (sinking)	Yes	CPM2C-S100C-DRT
			4 points: transistor (sourcing)	Yes	CPM2C-S110C-DRT

Note 1: For details on CPM2C PLCs, refer to the CPM2A/CPM2C Catalog (P049). Note 2: For details on Programmable Slave specifications, refer to the Programmable Slave Catalog (R071).

System Configuration





General Specifications and Performance Specifications

Item		Specifications			
Control method		Stored program method			
I/O control method		Cvclic scan method (Immediate refreshing can be performed with IOBF instruction.)			
Programming language					
Instruction length		1 step per instruction. 1 to 5 words per instruction			
Basic instructions					
Instructions	Special instructions	The instructions 195 variations			
	Special Instructions	10 Instructions, 100 variations			
time Created instructions		3. ve (LD instruction)			
Special instructions		A DOB words			
Program capaci	lly	4,uso works			
Maximum I/O points		Expansion I/O: 96 points (32-point Expansion I/O Unit × 3) CompoBus/S: 256 points (362 in total)			
Input bits		IR 00000 to IR 00915 (Bits not used for input bits can be used for work bits.)			
Output bits		IR 01000 to IR 01915 (Bits not used for output bits can be used for work bits.)			
CompoBus/S in	put bits	128 bits: IR 02000 to IR 02715 (Words IR 020 to IR 027)			
CompoBus/S ou	utput bits	128 bits: IR 03000 to IR 03715 (Words IR 030 to IR 037)			
Work bits		672 bits: IR 02800 to IR 02915 (Words IR 028 to IR 029) IR 03800 to IR 03915 (Words IR 038 to IR 039) IR 04000 to IR 04915 (Words IR 040 to IR 049) IR 20000 to IR 22715 (Words IR 200 to IR 227)			
Special bits (SR	area)	440 bits: SR 22800 to SR 25507 (Words IR 228 to IR 225)			
Temporary bits	(TR area)	8 bits (TR0 to TR7)			
Holding bits (HF	R area)	320 bits: HR 0000 to HR 1915 (Words HR 00 to HR19)			
Auxiliary bits (A	.R area)	384 bits: AR 0000 to AR 2315 (Words AR 00 to AR23) These include the CompoBus/S slave status flags (AR 04 to 07).			
Link bits (LR are	ea)	256 points: LR 0000 to LR 1515 (Words LR 00 to LR 15)			
Timers/Counters		256 timers/counters: TIM/CNT 000 to TIM/CNT 255 1-ms timers: TIMH 10-ms timers: TIMH 100-ms timers: TIM 1-s/10-s timers: TIML Decrementing counters: CNT Reversible counters: CNTR			
Data memory	Read/Write	2,048 words (DM 0000 to DM 2047) The Error Log is contained in DM 2000 to DM 2021.			
Duta memory	Read-only	456 words (DM 6144 to DM 6599)			
	PC Setup	56 words (DM 6600 to DM 6655)			
DeviceNet slave	functions	DeviceNet Remote I/O Link • Use up to 1,024 I/O points in the I/O Link. Explicit Message Communications • Any PC data area can be accessed from the master.			
Basic	Interrupt inputs	2 interrupts (Used for both counter mode interrupt inputs and quick-response inputs.)			
interrupt	Scheduled interrupts	1 interrupt			
Tunctions	High-speed counters	1 counter (20 kHz cingle-phase or 5 kHz 2-phase)			
the second	Counter interrupte	I counter (z) on iz single-philase to a kitz z-philase)			
Hign-speed counter	Interrupt inputs (counter				
functions	mode)	2 interrupts (Used for both external interrupt inputs and quick-response inputs.) 2 interrupts (Used for both external interrupt inputs and quick-response inputs.)			
	- out up interrupte	2 inputs			
Quick-response	inputs	(Used for both external interrupt inputs and counter mode interrupt inputs.) Min. input pulse width: 50 s max.			
Pulse output		2 points without acceleration/deceleration, 10 Hz to 10 kHz each, and no direction control; 1 point with trapezoid acceleration/deceleration, 10 Hz to 10 kHz, and direction control; 2 points with variable duty-ratio outputs			
Synchronized pulse control		1 point			
Input time cons	tant	An be set for CPU inputs and Expansion Unit inputs only.			
(ON response time = OFF response time)		(1 ms, 2 ms, 3 ms, 5 ms, 10 ms, 20 ms, 40 ms, or 80 ms)			
Clock		Equipped with clock (built-in RTC)			
Communications functions		Peripheral port: Supports Host Link, peripheral bus, no-protocol, or Programming Console connections. RS-232C port: Supports Host Link, no-protocol, 1:1 Link, or 1:1 NT Link connections.			
Memory protection		HR area, AR area, program contents, DM area contents, and counter values maintained during power interruptions.			
Memory backup		Non-volatile (flash) memory: Program, read-only DM area, and PC Setup			
меногу раскир		Memory backup (lithium battery; 2-year lifetime): DM area, HR area, AR area, and counter values			
Self-diagnostic functions		CPU errors (watchdog timer), memory errors, communications errors, setting errors, battery errors, and expansion I/O bus errors			
Program checks		No END instruction, programming errors (checked when operation is started)			
Programming	Programming Console	C200H-PRO27, CQM1-PRO01, or CQM1H-PRO01			
Devices	CX-Programmer	Windows edition			

* A Connecting Cable (CPM2C-CN111, CS1W-CN114, or CS1W-CN118) is required to connect to the communications (peripheral/RS-232C) port.

Communications Specifications

DeviceNet

Item	Specifications				
Communications protocol	Conforms to DeviceNet				
Connection form *1	Combination of multi-drop method and T-branch connections (for trunk and drop lines)				
Baud rate	500, 250, or 125 kbps				
Communications media	Special 5-wire cable (2 signal lines, 2 power supply lines, 1 shield line) 4-wire Special Flat Cable (2 signal lines and 2 power lines)				
	Using special 5-wire Flat Cable				
	Baud rate	Network length (max.)	Branch line length	Total branch line length	
	500 kbps	100 m max. *2	6 m max.	39 m max.	
	250 kbps	250 m max. *2	6 m max.	78 m max.	
Communications	125 kbps	500 m max. *2	6 m max.	156 m max.	
distance	Using special 4-wire Flat Cable				
	Baud rate	Network length (max.)	Branch line length	Total branch line length	
	500 kbps	75 m max.	6 m max.	35 m max.	
	250 kbps	150 m max.	6 m max.	48 m max.	
	125 kbps	265 m max.	6 m max.	135 m max.	
Communications power supply	24 VDC is supplied externally.				
Maximum number of nodes	64 (including Masters, Slaves, and the Configurator)				

Terminating resistance is required at both ends of the trunk line. This value applies when using Thick Cable for the trunk line. *1. *2.

If Thin Cable is used, the value will be 100 m max.

Cables for I/O Connector

96

• Cables for Connector - Terminal Conversion Units

Cable	Connected product	Remarks		
	XW2D-20G6	Slim type (with M3-screw terminal block)		
	XW2B-20G4	Flat cable connector type (with M3 (minus) terminal block)		

● CompoBus/S

Item		Specifications					
Communications		Special CompoBus/S protocol					
protocol							
Coding method		Manchester coding					
Connection form		Multi-drop method and T-branch connections *1					
Baud rate		High-speed Communications Mode: 750 kbps Long-distance Communications Mode: 93.75 kbps *2					
Com- muni- cations	High- speed Commu- nications Mode	0.5 ms (with 8 input and 8 output slaves connected) 0.8 ms (with 16 input and 16 output slaves connected)					
cycle time	Long-dis- tance Commu- nications Mode	4.0 ms (with 8 input and 8 output slaves connected) 6.0 ms (with 16 input and 16 output slaves connected)					
Commu media	unications	ications 2-wire cable (VCTF 0.75 x 2), 4-wire cable (VCTF 0.75 x 4), or Special Flat Cable					
Communications		2-wire VCTF cable					
		Communications mode	Main line length	Branch line length	Total branch line length		
		High-speed Communications Mode	100 m max.	3 m max.	50 m max.		
		Long-distance Communications Mode	500 m max.	6 m max.	120 m max.		
distanc	e	4-wire VCTF cable or Special Flat Cable					
		Communications mode	Main line length	Branch line length	Total branch line length		
		High-speed Communications Mode * 3	30 m max.	3 m max.	30 m max.		
		Long-distance Communications Mode * 4	Free branching (up to a total cable length of 200 m)				
Maximu of node	ım number s	32					
Error co checks	ontrol	Manchester code check, frame length check, and parity check					

*1. Connect external terminating resistance.

*2. *3.

Switched using DM area setting. (Default setting: 750 kbps.) If the number of slaves connected is 16 or less, the maximum main line length will be 100 m max., and the maximum total branch line length will be 50 m max. *4.

There are no restrictions on the branching configuration, main line length, branch line length, or total branch line length. Connect external terminating resistance to the node farthest from the master.

(Unit: mm)

Dimensions

CPM2C-S100C-DRT CPM2C-S110C-DRT



For detailed specifications, refer to the user's manual (Cat. No. W377).

Read and Understand This Catalog

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

Warranty and Limitations of Liability

WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall the responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

Application Considerations

SUITABILITY FOR USE

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the customer's application or use of the products.

At the customer's request, OMRON will provide applicable third party certification documents identifying ratings and limitations of use that apply to the products. This information by itself is not sufficient for a complete determination of the suitability of the products in combination with the end product, machine, system, or other application or use.

The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible uses of the products, nor is it intended to imply that the uses listed may be suitable for the products:

- · Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this catalog.
- Nuclear energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- · Systems, machines, and equipment that could present a risk to life or property.

Please know and observe all prohibitions of use applicable to the products.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCTS ARE PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

PROGRAMMABLE PRODUCTS

OMRON shall not be responsible for the user's programming of a programmable product, or any consequence thereof.

Disclaimers

CHANGE IN SPECIFICATIONS

Product specifications and accessories may be changed at any time based on improvements and other reasons.

It is our practice to change model numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the products may be changed without any notice. When in doubt, special model numbers may be assigned to fix or establish key specifications for your application on your request. Please consult with your OMRON representative at any time to confirm actual specifications of purchased products.

DIMENSIONS AND WEIGHTS

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

PERFORMANCE DATA

Performance data given in this catalog is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON Warranty and Limitations of Liability.

ERRORS AND OMISSIONS

The information in this document has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical, or proofreading errors, or omissions.

2009.8

In the interest of product improvement, specifications are subject to change without notice.

OMRON Corporation Industrial Automation Company

http://www.ia.omron.com/

(c)Copyright OMRON Corporation 2009 All Right Reserved.